

CONTEG DATASHEET

Complementary Systems

Standalone ACS

DP-ZM-ES-K (with keypad)

DP-ZM-ES-C (with card reader)

CONTEG, spol. s r.o.

Headquarters:

Na Vítězné pláni 1719/4
140 00 Prague 4
Czech Republic
Tel.: +420 261 219 182
Fax: +420 261 219 192

Production plant:

K Silu 2179
393 01 Pelhřimov
Czech Republic
Tel.: +420 565 300 300
Fax: +420 565 533 955

conteg@conteg.com
www.conteg.com

Local Branches/Offices

Austria / Germany /	
Switzerland:	+420 724 723 184
Benelux:	+32 477 957 126
Southeastern Europe:	+49 172 8484 346
Finland:	+358 50 414 1257
France / Italy / Maghreb:	+33 686 074 386
Middle East:	+971 4445 2838
Russia / CIS:	+7 495 967 3840
Saudi Arabia:	+966 594 30 13 08
Ukraine:	+380 674 478 240

The Self-Contained Electronic Locking System features a single component design that can be easily mounted into a standard panel prep, simplifying the integration of an electronic access solution into cabinet design, and eliminating the need for the wiring or connecting of separate components.



Standards and Specifications

- Unique electrical override feature
- Keyless entry simplifies access control
- Single component design enables easier integration, with no wiring
- Operates on three AA batteries
- Programming key offers simple, quick enrollment
- Low-power operation extends battery replacement interval (50k cycles)
- LED indicator provides visual feedback during programming and operation
- Secure cam lock mechanism
- Fits industry standard 25x150 panel prep
- Supports 1 programming key, up to 10 manager keys and Up to 10 user keys
- Supports up to 20 RFID cards or PINs
- PIN code can be four to seven digits
- Single point locking only

ORDERING CODES:

DP-ZM-ES-C	Standalone el. Latch with Card reader 13.56 MHz and battery case, verification by card only
DP-ZM-ES-K	Standalone el. Latch with keypad and battery case, verification by PIN only
DP-ZM-ES-PK	Programming key for standalone el. latch (red)
DP-ZM-ES-MK	Manager key for standalone el. latch (black)
DP-ZM-ES-UK	User key for standalone el. latch (black)
RMS-ACS-CMIF	13.56 MHz MIFARE® Classic Cards, package of 10pcs