



PREMIUM SERVER RSF BYTEline




RSF-42-80/100-BLA2

➤ The **PREMIUM Server RSF BYTEline** rack is designed as a dedicated server cabinet for data centers, equipment rooms and network or telecommunication closets. The RSF's heavy-duty, all-welded design and 1500 kg load rating make it ideal for accommodating heavy equipment within a standard rack footprint. 19" RSF server racks also offer top-of-the-line cabling support, with unbeatable access.



MAIN ADVANTAGES

- All-features-included server rack
- Unmatched 86% door perforation ratio decreases server fan power consumption
- Advanced door design
- Dedicated server design
- Tailored for typical data center projects with hot/cold aisle or contained aisle layouts
- Safety Lift-Off Hinge for tool-less door assembly/disassembly
- Fully compatible with Zero U (0U) PDUs

COLOR SAMPLER:  RAL 9005

 RAL 7035

DESCRIPTION:

Sizes

- Height: 42U
- Width: 600, 800 mm
- Depth: 1000, 1200 mm

Construction

- Welded-frame design
- 1.5 & 2.0 mm sheet steel

Load rating

- 1500 kg balanced load
- 2 pairs of sliding 19" vertical A-type (600 or 800 mm) extrusions without horizontal holders (for 800 mm provide additional 24U of installation space), adjustable from inside

IP rating

- Standard IP00

Colors

- Standard RAL 9005 and 7035

Front door

- Vented door – perforation rate 86%
- Swivel handle lock – DIN profile, universal key 333, multipoint
- Door opening angle 180°
- Easy re-hanging to open on right or left

Rear door

- Vented door – perforation rate 86%
- Swivel handle lock – DIN profile, universal key 333, multipoint

Side panels

- Removable with locks or without side panels

Top plate

- Single-piece design, removable

- 4" (100 mm) rounded cable entry in every corner covered by plastic cap
- 300x100 mm cable entries covered with removable blank sheet steel panels

Bottom plate

- No bottom plate

Feet

- Adjustable feet standard

Adaptation

- Adaptable for installation of 21" equipment (upon request, for 800 mm width only)

Other

- Installable in blocks with DP-DR-UNI (ordered separately)
- GND/earthing kit included

ORDERING INFORMATION FOR RSF BYTEline: The configurations presented below cannot be changed. Please note that all RSF BYTEline RACKS ARE DELIVERED FULLY ASSEMBLED and palletized!

RSF BYTEline – DIMENSIONS AND FEATURES

Code	H (in U)	Dimensions (mm)		Front door	Rear door			Side panels		Extrusions	
		W	D	Vented door	Vented door	Vertically divided vented door	Two side panels	Without	A-type	A-type with additional 12×2U	
RSF-42-60/100-BLA1-X	42	600	1000	yes	yes	–	yes	–	yes	–	
RSF-42-60/100-BLA4-X	42	600	1000	yes	yes	–	–	yes	yes	–	
RSF-42-60/100-BLA7-X	42	600	1000	yes	–	yes	yes	–	yes	–	
RSF-42-60/120-BLA8-X	42	600	1200	yes	–	yes	yes	–	yes	–	
RSF-42-60/100-BLA10-X	42	600	1000	yes	–	yes	–	yes	yes	–	
RSF-42-60/120-BLA11-X	42	600	1200	yes	–	yes	–	yes	yes	–	
RSF-42-80/100-BLA2-X	42	800	1000	yes	yes	–	yes	–	–	yes	
RSF-42-80/100-BLA3-X	42	800	1000	yes	–	yes	yes	–	–	yes	
RSF-42-80/100-BLA5-X	42	800	1000	yes	yes	–	–	yes	–	yes	
RSF-42-80/100-BLA6-X	42	800	1000	yes	–	yes	–	yes	–	yes	
RSF-42-80/120-BLA9-X	42	800	1200	yes	–	yes	yes	–	–	yes	
RSF-42-80/120-BLA12-X	42	800	1200	yes	–	yes	–	yes	–	yes	

Substitute X with desired color: B – RAL 7035 (light gray) or H – RAL 9005 (black). Please note that RSF-BYTEline series differs from standard RSF rack configurations.

Recommended accessories



Air separation frame

More information [on page 91](#)



RAMOS Ultra

More information [on page 97](#)



19" blank and fast blank panels

More information [on page 90](#)

www.conteg.com



CONTEG, spol. s r.o.

Headquarters:

Na Vítězské pláni 1719/4
140 00 Prague 4
Czech Republic
Tel.: +420 261 219 182
conteg@conteg.com
www.conteg.com

Production plant:

K Silu 2179
393 01 Pelhřimov
Czech Republic
Tel.: +420 565 300 300

Local Branches/Offices:

Austria/Germany/Switzerland:	+420 261 219 182
Benelux:	+31 76 5420 709
Southeastern Europe:	+49 172 8484 346
Finland:	+358 50 414 1257
France/Italy/Maghreb:	+33 1 60 04 55 90
Middle East:	+971 55 508 3241
Russia/CIS:	+7 495 967 3840
Saudi Arabia:	+966 54 000 2341

CONTEG